

MDF KIT ACTIVATOR



MDF KIT ACTIVATOR is an adhesive set which consists of high viscosity cyanoacrylate adhesive and activator.

PROPERTIES

- High bonding strength
- Suitable for use on vertical surfaces as it will not drip or slump.
- It is particularly suited to bonding difficult substrates which have a porous or uneven nature since it increases bonding strength by preventing the adhesive to be absorbed by the surface.

APPLICATIONS

- It is particularly used for fixing and repairing wooden parts.
- Suitable for MDF, wood, chip wood, rubber, most plastics, leather etc.
- Especially suitable for the applications where cure speed needs to be accelerated.

CHEMICAL ANCHOR



CHEMICAL ANCHOR is a quick curing reaction resin mortar for high loads in almost all building materials. It is used with special application gun and static mixer.

PROPERTIES

- Excellent bonding of the mortar enables very high loads in concrete.
- It can be used in many types of solid Stones.
- Secure anchoring in hollow bricks.
- It cures rapidly.
- Scaled cartridge enables accurate dosage of the compound
- Non-sagging; It can be applied vertically.
- Resistant to permanent temperature of 80 °C (Temporary 110 °C)

APPLICATIONS

- Heavy load-carrying attachments in solid stone and concrete.
- Repair mortar or adhesive mortar for concrete components.
- Attachment of anchor rods, threaded collars, reinforcement bars, profiles etc.
- Medium-load applications in hollow-bricks.
- Fixing of:
 - Wooden constructions
 - Metal constructions
 - Metal profiles
 - Sanitary fittings
 - Pipe connections
 - Projecting roofs
 - Facades
 - Cable trays
 - Railings
 - Staircases
 - Gates
 - Window elements



EUROFIX®

EUROFIX

Bayi Kağıdı



EUROFIX®

MULTI PURPOSE PU FOAM



MULTI PURPOSE PU FOAM is a single-component, moisture-curing and self-expanding aerosol polyurethane foam. It is designed for easy dispensing through the straw adapter included with each can. It does not contain any propellant gases that are harmful to the ozone layer.

PROPERTIES

- Excellent adhesion & filling capacity and high thermal & acoustical insulation value.
- Excellent mounting capacity and stability.
- Adheres to almost all building materials with the exception of surfaces such as polyethylene, Teflon, silicone and surfaces contaminated with oils and greases, mold release agents and similar materials.
- Mould-proof, water-proof, over paintable.
- Cured foam dries rigid and can be trimmed, shaped and sanded.

APPLICATIONS

- Fixing and insulating of door and window frames.
- Filling and sealing gaps, joints and cavities.
- Filling of penetrations in walls.
- Insulating electrical outlets and water pipes.

PROFESSIONAL PU FOAM



PROFESSIONAL PU FOAM is single-component PU foam used with an applicator gun and features higher yield, easier application and reusability. It does not contain any propellant gases which are harmful to the ozone layer.

PROPERTIES

- Excellent adhesion & filling capacity and high thermal & acoustical insulation value.
- Economical consumption thanks to precise application.
- High yield up to 45 liters depending on temperature and humidity.
- Conforms to fire class B3 according to DIN 4102-1.
- Mould-proof, water-proof and over paintable.

APPLICATIONS

- Fixing and insulating of door and window frames.
- Filling and sealing of gaps, joints and cavities.
- Filling of penetrations in walls.
- Insulating electrical outlets and water pipes.

UNIVERSAL SILICONE



UNIVERSAL SILICONE is an acid-curing, one-component silicone sealant for a range of general sealing and glazing applications. It's suitable for use on common non-porous building materials.

PROPERTIES

- Stays permanently elastic after curing
- Acetoxy curing system
- Antibacterial
- Very good adhesion on common building materials and non-porous surfaces
- Resistance to aging, cracking and discoloring
- Resistant to many chemicals, cleaning agents and detergents
- Can be applied in any season
- Typical acetic smell during curing

APPLICATIONS

- General sealing and glazing applications
- Sealing around windows and doors
- Sealing in DIY applications
- Sanitary applications
- Connection and expansion joints
- Sealing electric, telephone etc. sockets and switches

ACRYLIC SEALANT



ACRYLIC SEALANT is one-component universal acrylic sealant suitable for filling cracks and joints both indoors and outdoors. It's a cost-effective plastic-elastic sealant ideal for particularly static joints.

PROPERTIES

- Over paintable
- Can be used on all porous surfaces such as brick, concrete, wood etc.
- Very easy to apply and clean
- Water-proof after curing
- Resistant to weathering such as rain, snow and sunlight
- Does not contain any solvents
- No odour

APPLICATIONS

- Sealing of low and medium movement joints between various construction materials (wood, concrete, brick etc.)
- Filling cracks in walls and on ceilings.
- Sealing joints between windows, walls, doors etc.

SILICONIZED ACRYLIC SEALANT



SILICONIZED ACRYLIC SEALANT is one-component general purpose acrylic-dispersion based sealant reinforced with silicone emulsion. It has superior adhesion and good elasticity.

PROPERTIES

- Permanently elastic after cure
- Can be used on all porous surfaces such as brick, concrete wood etc.
- Very easy to apply and clean
- Water-proof after curing
- Resistant to weathering such as rain, snow and sunlight
- Solvent-free
- Over paintable
- No odour

APPLICATIONS

- Sealing of low and medium movement joints between various construction materials (wood, concrete, brick etc.)
- Sealing joints between windows, walls, doors etc.
- Filling cracks in walls and on ceilings.

MARINE ADHESIVE



MARINE ADHESIVE is a one-component polyurethane wood adhesive. It cures with moisture in the air and in the wood.

PROPERTIES

- Easy application, low viscosity
- Excellent bond strength
- Fast drying
- Water resistant (D4-DIN EN204)
- Can be used on slightly humid surfaces
- Resistant to temperature extremes
- Resistant to moisture and chemicals

APPLICATIONS

- Fixing and gluing wooden elements to other various porous and non-porous elements as wood, metal, concrete, polystyrene foam and other plastics.
- Furniture and boat production
- All bonding applications that need a high water resistance