

TECNICAL DATA SHEET (TDS)

WALLPAPER & BORDURE ADHESIVE

1 - DESCRIPTION

Wallpaper & Bordure Adhesive is a cellulosic polymer based, water soluble powder used in sticking of cellulose based paper materials.

2 - PROPERTIES

- Easy to apply.
- Allows time for positioning.
- Makes future removal quick and easy.
- Dissolves in water with ease.
- Can be cleaned with a sponge and water

3 - APPLICATIONS

Sticking wallpapers, pre-pasted borders, posters, placards etc.

4 - INSTRUCTIONS

Add the adhesive slowly, in preferably warm, water in accordance with the figures shown below. Stir the mixture and allow the adhesive dissolve in the water. Make sure that substrates are clean, dry and smooth. Roll the mixture to the back of wallpapers.

5- PACKAGING

Product	Volume	Package
Wallpaper & Bordure Adhesive	125 gr.	144
Wallpaper & Bordure Adhesive	200 gr.	60
Wallpaper & Bordure Adhesive	500 gr.	24
Wallpaper & Bordure Adhesive	1000 gr.	12

6- STOROGE AND SHELF LIFE

24 months in unopened cartridge if stored under dry and cool conditions

7- SAFETY

- Storage over 25 °C and below 5 °C shortens shelf-life.
- Partially used cartridges can be reused easily by changing the static mixer.

01 / 2012 Rev.01 Sayfa 1





8- TECHNICAL PROPERTIES

Basis	: Carboxymethyl cellulose	
Appearance	: Powder	
Colour	: White to creamy	
Viscosity	: 150 - 300 Cp	cps at 20°C (Spindle No 4, 12 rpm)
Temperature Resistance	: -20°C to +70°C	
Application Temperature	: +5 °C to +35 °C	

Application Ratios

200g for packages

Paper type	The amount of water	Surface
Thin	6.5 Liter	20-25 m ²
Embossed	5 Liter	15-20 m ²
Vinly	3.6 Liter	13-18 m ²

500g for packages

Paper type	The amount of water	Surface
Thin	12 Liter	40 m ²
Embossed	10 Liter	33 m ²
Vinly	8 Liter	27 m ²

01 / 2012 Rev.01 Sayfa 2